



AEC DESCALING SYSTEM & FLUID FOR TCUS

AEC is proud to offer a proven method to remove scale, lime, and rust deposits—the AEC Descaling System and fluid. The descaling system is designed to work with AEC temperature control units, or any other brand, as well as other water equipment where clogging can reduce efficiency and performance.

The descaling system is portable and easy to operate. The system operates on any 110V outlet and connects easily to your processes with quick-attach hoses. It is designed specifically to circulate AEC descaling fluid, which is a tar oil-based liquid with wetting and penetrating agents.



Descaling Unit

STANDARD FEATURES

- Quick-attach hose fitting
- 3/4" delivery and return connections
- 3/4" NPT drain on side of tank
- Industrial-duty 1/2 hp open drip-proof motor with thermal overload protection
- Easy-access start/stop buttons
- Y strainer with accessible cleaning port
- 9 ft. grounded power cord
- 15 gallon heavy-duty, non-corrosive plastic reservoir with removable lid
- Descaling fluid is USDA-approved
- Will not erode, pit, oxidize, or harm metal and other materials
- Non-toxic, non-injurious, non-corrosive, non-flammable, and can be disposed of in normal plant sewers

OPTIONAL FEATURES

- Descaling fluid, 5, 30, or 55 gallons

SPECIFICATIONS

Model	Operating temp	Motor, hp	Voltage	Full Load Amps	Dimensions, in.	Ship. weight, lbs.
Descaling System	Ambient	0.5	115/1/60	8.4	22L x 16W x 38H	115

